

**Application**

Upholstery

**Content**

88% Polyester, 12% Tekloom® TPE (Graffiti-Free®)  
\*Patented, High Performance Fused Textile

**Width**

54"

**Repeat**

1" H, 1.75" V

**General Characteristics**

Abrasion : Exceeds 1 Million Double Rubs  
(Wyzenbeek)† Hydrolysis Resistance : 15+ weeks  
- ISO1419:1995, Method C, Tropical Test

Innovative technology to Combine Textile with the  
Performance of Coated Fabric

Ink/Stain Resistant, Liquid Barrier, Bleach Cleanable

Meets or Exceeds all ACT Heavy Duty Performance  
Guidelines for Upholstery

**Flammability**

CA Bulletin 117-2013, UFAC/NFPA 260-Class 1  
IMO A652 (16) 8.2

**Environmental**

DMF Free, PVC/Phthalates Free, PFC Free, FR/Anti-  
Microbial Additives Free  
\*Complies with REACH, Prop 65, HHI & CAL 01350

**Maintenance††**

W/S, Bleach (10:1)

**Warranty**

Please refer to our Terms of Sales for warranty  
information.



Field



† Abrasion test results exceeding ACT Performance Guidelines are not an indicator of product lifespan. Multiple factors affect fabric durability and appearance retention.

†† Tekloom protects the woven fabric with a patented clear TPE layer. All approved cleaning chemicals should stay on Tekloom surface. Avoid soaking the seamed area to prevent the cleaning chemicals from entering the base, which might damage the product integrity.